



## TECHNICAL SPECIFICATON

## tretford Carpet

### CUSTOM RUGS

Construction (*INTERLIFE Quality*)

Loop (ondule)

Pile Material

70% Goat Hair

30% Polyamid 6

Primary Backing

Jute

Secondary Backing

Felt (recycled PET)

Pile Insert Weight

c. 1200 g/m<sup>2</sup>

Pile Height

c. 5 mm

Total Thickness

c. 9,0 mm

Dimensions

c. 200 cm

Total Weight

c. 3,5 kg/m<sup>2</sup>

Comfort class

LC2

Stress Range

23 / 33 (strong)

Colour Fastness to Light

5

Colour Fastness to Water

4-5

Flammability

Cfl-s1 (B1)

Thermal Resistance

c. 0,10 m<sup>2</sup> K/W

Impact Noise Reduction

c. 22 dB

Anti-Static Rating

- 1,3 kV

Vertical Resistance

c. 10<sup>9</sup> Ω

Cut Resistance

yes

Suitable for Office Chairs

yes

Suitable for Stairs

yes \*

Suitable for WW-Floorheating

yes

Suitable for house dust allergic persons

yes

Country of Manufacture

Germany

\* in connection with tretford stair-profiles



Colour variations to samples are possible. 2/2023, subject to modification.