



TECHNICAL SPECIFICATON

tretford INTERLIFE

	SHEET	TILES	FLOORBOARDS
Construction	Loop (ondule)	Loop (ondule)	Loop (ondule)
Pile Material	70% Goat Hair 30% Polyamid 6	70% Goat Hair 30% Polyamid 6	70% Goat Hair 30% Polyamid 6
Backing	Jute	Non-woven	Non-woven
Pile Insert Weight	c. 1200 g/m ²	c. 1200 g/m ²	c. 1200 g/m ²
Pile Height	c. 5 mm	c. 5 mm	c. 5 mm
Total Thickness	c. 7,2 mm	c. 8,0 mm	c. 8,0 mm
Dimensions	c. 200 cm	c. 50 x 50 cm	c. 25 x 100 cm
Total Weight	c. 3,1 kg/m ²	c. 3,7 kg/m ²	c. 3,7 kg/m ²
Comfort class	LC2	LC2	LC2
Stress Range	23 / 33 (strong)	23 / 33 (strong)	23 / 33 (strong)
Colour Fastness to Light	5	5	5
Colour Fastness to Water	4-5	4-5	4-5
Flammability	Cfl-s1 (B1)	Cfl-s1 (B1)	Cfl-s1 (B1)
Thermal Resistance	c. 0,10 m ² K/W	c. 0,11 m ² K/W	c. 0,11 m ² K/W
Impact Noise Reduction	c. 22 dB	c. 24 dB	c. 24 dB
Anti-Static Rating	- 1,3 kV	- 1,3 kV	- 1,3 kV
Vertical Resistance	c. 10 ⁹ Ω	c. 10 ⁹ Ω	c. 10 ⁹ Ω
Cut Resistance	yes	yes	yes
Suitable for Office Chairs	yes	yes	yes
Suitable for Stairs	yes *	no	no
Suitable for WW-Floorheating	yes	yes	yes
Suitable for house dust allergic persons	yes	yes	yes
Country of Manufacture	Germany	Germany	Germany

* in connection with tretford stair-profiles



Colour variations to samples are possible. 12/2018, subject to modification.