

# FIRST SWAY comfortback

<p>CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR</p>	<p>Tufted 1/12" Loop Tufté 1/12" Bouclé Getuftet 1/12" Schlinge Getuft 1/12" Luspool</p>	<p>FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG</p>	<p>EN 13501-1 B<sub>f</sub>-s1</p>
<p>PILE MATERIAL COUCHE D'USURE POLMATERIAAL POOLMATERIAAL</p>	<p>100% PA6 Solution Dyed Nylon</p>	<p>FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID</p>	<p>ISO 105-B02 ≥ 7</p>
<p>SECONDARY BACKING DOSSIER RÜCKENAUSSTATTUNG RUG</p>	<p>comfortBack: shock absorbing and noise reducing carpet tile backing, made from 90% recycled polyester felt</p>	<p>RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID</p>	<p>EN ISO 105-X12 ≥ 4</p>
<p>TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT</p>	<p>Ca. 4.600 g/m<sup>2</sup></p>	<p>COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID</p>	<p>EN ISO 105-E01 ≥ 4</p>
<p>PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT</p>	<p>Ca. 590 g/m<sup>2</sup></p>	<p>THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLABWIDERSTAND WARMTEDOORLAATWEERSTAND</p>	<p>ISO 8302 0,126 m<sup>2</sup>K/W</p>
<p>PILE ABOVE BACKING POIDS DE VELOURS UTILE POLNUTZSCHICHTGEWICHT NUTTIG POOLGEWICHT</p>	<p>Ca. 360 g/m<sup>2</sup></p>	<p>IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG- MAB GELUIDSISOLATIE</p>	<p>ISO 10140 ΔL<sub>w</sub>: 29 dB</p>
<p>TOTAL HEIGHT ÉPAISSEUR TOTALE GESAMTDICKE TOTAAL DIKTE</p>	<p>Ca. 8,9 mm</p>	<p>SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE</p>	<p>ISO 354 α<sub>w</sub>: 0,30</p>
<p>PILE HEIGHT ÉPAISSEUR DU VELOURS POLDICKE POOLHOOGTE</p>	<p>Ca. 2,7 mm</p>	<p>PERMANENT ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH</p>	<p>ISO 6356 ≤ 2 kV</p>
<p>PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTHEIT POOLDICHTHEID</p>	<p>Ca. 0,124 g/cm<sup>3</sup></p>	<p>TRANSVERSAL RESISTANCE RÉSISTANCE TRANSVERSALE DURCHGANGSWIDERSTAND DOORGANGSWEERSTAND</p>	<p>ISO/DIS 10965 ≤ 10<sup>11</sup> Ohm</p>
<p>TUFT DENSITY NOMBRE DE TOUFFES NOPPENZAHL AANTAL PUNTEN</p>	<p>Ca. 202.000 /m<sup>2</sup></p>	<p>SIZE &amp; PACKING DIMENSION &amp; EMBALLAGE ABMESSUNG &amp; VERPACKUNG AFMETINGEN &amp; VERPAKKING</p>	<p>50 cm x 50 cm box: 4 m<sup>2</sup> pallet: 20 boxes</p>
<p>CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE</p>	<p>EN 1307 33 - LC1</p>	<p>NUMBER OF COLOURS NOMBRE DE COLORIS ANZAHL DER FARBEN AANTAL KLEUREN</p>	<p>11</p>
<p>CASTOR CHAIR SUITABILITY EMPLOI CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID</p>	<p>EN ISO 4918 A : continuous use</p>	<p>DIMENSIONAL STABILITY STABILITÉ DIMENSIONNELLE DIMENSIONSTABILITÄT DIMENSIONELE STABILITEIT</p>	<p>EN 986 max. 0,2%</p>
		<p>GUT-NR</p>	<p>tbc</p>
		<p>LEED®</p>	<p>Product contributes toward satisfying Credits under LEED®.*</p>
		<p>DGNB</p>	<p>modulyss is member of DGNB, the German Sustainable Building Council.</p>

\* For more information, see the modulyss sustainable datasheets. - Remark: Products are not reviewed under LEED®, LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products of brands. The LEED® green building certification program is the nationally accepted benchmark for the design, construction, and operation of green buildings. For more information on LEED®, visit [www.usgbc.org/contact](http://www.usgbc.org/contact).

